(in accordance with Regulation (EU) 2015/830)

# **MAXSEAL SUPER**

Version:8 Page 1 of 8 **Revision date: 4/11/2021** Print date: 21/01/2017

DRIZOR

Construction Products

## SECTION 1: IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING.

#### 1.1 Product identifier.

Product Name: MAXSEAL SUPER

1.2 Relevant identified uses of the mixture and uses advised against.

Mortar Cement

#### Uses advised against:

Uses other than those recommended.

- 1.3 Details of the supplier of the safety data sheet.
- 1.3 Details of the supplier of the safety data sheet.

Company: HANMA INVESTMENTS P/L ABN: 26 086 715 264

Address: Unit4/92 Bryant Street

City: Padstow **NSW** Australia Province:

Telephone: (61) (0) 2 9771 0011 E-mail: hans@hanma.com.au

1.4 Emergency telephone number: 1300 303 301 (Only available during office hours

# **SECTION 2**

### 2.1 Classification of the mixture.

In accordance with Regulation (EU) No 1272/2008:

Eye Irrit. 2: Causes serious eye irritation. STOT SE 3: May cause respiratory irritation.

Skin Irrit. 2: Causes skin irritation.

Skin Sens. 1: May cause an allergic skin reaction.

### 2.2 Label elements.

### Labelling in accordance with Regulation (EU) No 1272/2008:

Pictograms:



# Signal Word:

### Warning H statements:

H315

Causes skin irritation. May cause an allergic skin reaction. H317 H319 Causes serious eye irritation. May cause respiratory irritation. H335

P statements:

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P321 Specific treatment (see ... on this label).

P337+P313 If eye irritation persists: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse. P403+P233 Store in a well-ventilated place. Keep container tightly closed.

-Continued on next page.-

(in accordance with Regulation (EU) 2015/830)

# **MAXSEAL SUPER**



 Version: 8
 Page 2 of 8

 Revision date: 4/11/2021
 Print date: 21/01/2017

P501 Dispose of contents/container to ...

Contains:

Cement, portland, chemicals

#### 2.3 Other hazards.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

#### 3.1 Substances.

Not Applicable.

#### 3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	specific concentration limit
CAS No: 65997-15-1 EC No: 266-043-4	Cement, portland, chemicals	20 - 50 %	Eye Irrit. 2, H319 - STOT SE 3, H335 - Skin Irrit. 2, H315 - Skin Sens. 1, H317	-

<sup>(\*)</sup> The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

## **SECTION 4: FIRST AID MEASURES.**

IRRITANT PREPARATION. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

#### 4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

### Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

### **Eve contact**

If wearing contact lenses, remove them. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.

#### **Skin contact**

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. **NEVER** use solvents or thinners.

# Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

# 4.2 Most important symptoms and effects, both acute and delayed.

Irritant Product, repeated or prolonged contact with skin or mucous membranes can cause redness, blisters or dermatitis, inhalation of spray mist or particles in suspension may cause irritation of the respiratory tract, some symptoms may not be immediate. Can cause allergic reactions.

#### 4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

(in accordance with Regulation (EU) 2015/830)

# **MAXSEAL SUPER**





### **SECTION 5: FIREFIGHTING MEASURES.**

The product does not present any particular risk in case of fire.

### 5.1 Extinguishing media.

## Recommended extinguishing methods.

Extinguisher powder or CO<sub>2</sub>. In case of more serious fires, also alcohol-resistant foam and water spray. Do not use a direct stream of water to extinguish.

#### 5.2 Special hazards arising from the mixture.

### Special risks.

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

#### 5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways.

#### Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and gloves.

### SECTION 6: ACCIDENTAL RELEASE MEASURES.

### 6.1 Personal precautions, protective equipment and emergency procedures.

For exposure control and individual protection measures, see section 8.

### 6.2 Environmental precautions.

Prevent the contamination of drains, surface or subterranean waters, and the ground.

# ${\bf 6.3~Methods}$ and material for containment and cleaning up.

The contaminated area should be immediately cleaned with an appropriate de-contaminator. Pour the decontaminator on the remains in an opened container and let it act various days until no further reaction is produced.

#### 6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

# SECTION 7: HANDLING AND STORAGE.

#### 7.1 Precautions for safe handling.

For personal protection, see section 8. Never use pressure to empty the containers. They are not pressure-resistant containers. In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Keep the product in containers made of a material identical to the original.

### 7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 35° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

The product is not affected by Directive 2012/18/EU (SEVESO III).

## 7.3 Specific end use(s).

Not available.

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

(in accordance with Regulation (EU) 2015/830)

# **MAXSEAL SUPER**

 Version:8
 Page 4 of 8

 Revision date: 4/11/2021
 Print date: 21/01/2017

### 8.1 Control parameters.

The product does NOT contain substances with Professional Exposure Environmental Limit Values. The product does NOT contain substances with Biological Limit Values.

# 8.2 Exposure controls.

# Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %			
Uses:	Mortar Cement			
Breathing protection:				
PPE:	Filter mask for protection against gases and particles.			
Characteristics:	«CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.			
CEN standards:	EN 136, EN 140, EN 405			
Maintenance:	Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor.  Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach			
Observations:	the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.			
Filter Type needed:	A2			
Hand protection:				
PPE: Characteristics:	Protective gloves against chemicals.  «CE» marking, category III.			
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420			
Maintenance:	Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.			
Observations:	Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight.  Always use with clean, dry hands.			
Material: F	PVC (polyvinyl chloride) Breakthrough time (min.): Material thickness (mm):			
Eye protection:				
PPE: Characteristics:	Face shield.  «CE» marking, category II. Face and eye protector against splashing liquid.			
CEN standards:	EN 165, EN 166, EN 167, EN 168			
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Make sure that mobile parts move smoothly.			
Observations:	Face shields should offer a field of vision with a dimension in the central line of, at least, 150 mm vertically once attached to the frame.			
Skin protection:	<u>,                                      </u>			
PPE: Characteristics:	Anti-static protective clothing.  «CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.			
CEN standards:	EN 340, EN 1149-1, EN 1149-2, EN 1149-3, EN 1149-5			
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.  The protective clothing should offer a level of comfort in line with the level of protection provided in			
Observations:	terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use.			
PPE:	Anti-static safety footwear.			
Characteristics:	«CE» marking, category II.			
CEN standards:	EN ISO 13287, EN ISO 20344, EN ISO 20346			
Maintenance:	The footwear should be checked regularly			
Observations:	The level of comfort during use and acceptability are factors that are assessed very differently depending on the user. Therefore, it is advisable to try on different footwear models and, if possible, different widths.			

DRIZORO

**Construction Products** 

(in accordance with Regulation (EU) 2015/830)

# **MAXSEAL SUPER**

Version: 8

Revision date: 4/11/2021



Page 5 of 8 Print date: 21/01/2017

# SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

### 9.1 Information on basic physical and chemical properties.

Appearance: Odourless powder with characteristic colour

Colour: N.A./N.A. Odour:N.A./N.A.

Odour threshold: N.A./N.A.

pH:11 -13.5

Melting point: > 1000 °C °C Boiling Point: N.A./N.A. Flash point: N.A./N.A. Evaporation rate: N.A./N.A. Inflammability (solid gas): N

Inflammability (solid, gas): N.A./N.A.
Lower Explosive Limit: N.A./N.A.
Upper Explosive Limit: N.A./N.A.
Vapour pressure: N.A./N.A.
Vapour density:N.A./N.A.
Relative density:1.30 g/cm<sup>3</sup>
Solubility:N.A./N.A.
Liposolubility: N.A./N.A.

Hydrosolubility: En contacto con agua precipita Partition coefficient (n-octanol/water): N.A./N.A.

Auto-ignition temperature: N.A./N.A. Decomposition temperature: N.A./N.A.

Viscosity: N.A./N.A.

Explosive properties: N.A./N.A. Oxidizing properties: N.A./N.A.

N.A./N.A.= Not Available/Not Applicable due to the nature of the product

### 9.2 Other information.

Pour point: N.A./N.A. Blink: N.A./N.A.

Kinematic viscosity: N.A./N.A.

N.A./N.A.= Not Available/Not Applicable due to the nature of the product

## SECTION 10: STABILITY AND REACTIVITY.

### 10.1 Reactivity.

The product does not present hazards by their reactivity.

### 10.2 Chemical stability.

Unstable in contact with:

- Acids.

### 10.3 Possibility of hazardous reactions.

Neutralization can occur on contact with acids.

# 10.4 Conditions to avoid.

- Avoid contact with acids.

### 10.5 Incompatible materials.

Avoid the following materials:

- Acids.

### 10.6 Hazardous decomposition products.

Depending on conditions of use, can be generated the following products:

- Corrosive vapors or gases.

(in accordance with Regulation (EU) 2015/830)

# **MAXSEAL SUPER**

Version:8

**Revision date: 4/11/2021** 



Page 6 of 8 Print date: 21/01/2017

### SECTION 11: TOXICOLOGICAL INFORMATION.

IRRITANT PREPARATION. Splatters in the eyes can cause irritation.

IRRITANT PREPARATION. The inhalation of spray mist or suspended particulates can irritate the respiratory tract. It can also cause serious respiratory difficulties, central nervous system disorders, and in extreme cases, unconsciousness.

IRRITANT PREPARATION. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

#### 11.1 Information on toxicological effects.

There are no tested data available on the product.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

Splatters in the eyes can cause irritation and reversible damage.

a) acute toxicity;

Not conclusive data for classification.

b) skin corrosion/irritation;

Product classified:

Skin irritant, Category 2: Causes skin irritation.

c) serious eye damage/irritation;

Product classified:

Eye irritation, Category 2: Causes serious eye irritation.

d) respiratory or skin sensitisation;

Product classified:

Skin sensitiser, Category 1: May cause an allergic skin reaction.

e) germ cell mutagenicity;

Not conclusive data for classification.

f) carcinogenicity;

Not conclusive data for classification.

g) reproductive toxicity;

Not conclusive data for classification.

h) STOT-single exposure;

Product classified:

Specific target organ toxicity following a single exposure, Category 3:

i) STOT-repeated exposure;

Not conclusive data for classification.

j) aspiration hazard;

Not conclusive data for classification.

### SECTION 12: ECOLOGICAL INFORMATION.

### 12.1 Toxicity.

No information is available regarding the ecotoxicity of the substances present.

### 12.2 Persistence and degradability.

No information is available about persistence and degradability of the product.

### 12.3 Bioaccumulative potencial.

No information is available regarding the bioaccumulation of the substances present.

### 12.4 Mobility in soil.

No information is available about the mobility in soil.

The product must not be allowed to go into sewers or waterways.

Prevent penetration into the ground.

(in accordance with Regulation (EU) 2015/830)

# MAXSEAL SUPER

Version: 8 **Revision date: 4/11/2021** 

Print date: 21/01/2017



# 12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

#### 12.6 Other adverse effects.

No information is available about other adverse effects for the environment.

### SECTION 13 DISPOSAL CONSIDERATIONS.

#### 13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

### **SECTION 14: TRANSPORT INFORMATION.**

Transportation is not dangerous. In case of road accident causing the product's spillage, proceed in accordance with point 6.

#### 14.1 UN number.

Transportation is not dangerous.

#### 14.2 UN proper shipping name.

Description:

ADR: Transportation is not dangerous. IMDG: Transportation is not dangerous. ICAO: Transportation is not dangerous.

### 14.3 Transport hazard class(es).

Transportation is not dangerous.

## 14.4 Packing group.

Transportation is not dangerous.

### 14.5 Environmental hazards.

Transportation is not dangerous.

# 14.6 Special precautions for user.

Transportation is not dangerous.

### 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code.

Transportation is not dangerous.

### **SECTION 15: REGULATORY INFORMATION.**

### 15.1 Safety, health and environmental regulations/legislation specific for the mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

Volatile organic compound (VOC)

VOC content (p/p): 0 % VOC content: 0 g/l

The product is not affected by Directive 2012/18/EU (SEVESO III).

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

(in accordance with Regulation (EU) 2015/830)

# **MAXSEAL SUPER**

Version: 8

Revision date: 4/11/2021



Page 8 of 8 Print date: 21/01/2017

#### 15.2 Chemical safety assessment.

There has been no evaluation a chemical safety assessment of the product.

### **SECTION 16: OTHER INFORMATION.**

Complete text of the H phrases that appear in section 3:

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.

#### Classification codes:

Eye Irrit. 2: Eye irritation, Category 2

STOT SE 3: Specific target organ toxicity following a single exposure, Category 3

Skin Irrit. 2 : Skin irritant, Category 2 Skin Sens. 1 : Skin sensitiser, Category 1

Sections changed compared with the previous version:

1,2,7,14,16

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

CEN: European Committee for Standardization.

PPE: Personal protection equipment.

Key literature references and sources for data:

http://eur-lex.europa.eu/homepage.html

http://echa.europa.eu/

Regulation (EU) 2015/830.

Regulation (EC) No 1907/2006.

Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.

# SCIENTIFIC WATERPROOFING PRODUCTS PTY LTD ABN:78 155 659 948

4/92 Bryant Street PADSTOW NSW 2211 Phone 02 9771 0011 PO BOX 694 PADSTOW NSW 2211

http://www.swppl.com.au/

Contact:e-mail: info@swppl.com.au