

Specs: 27.00Specs23

TREATING EFFLORESCENCE IN GROUT LINES

Efflorescence through grout on tiled balconies.

We recommend the following: -



- a. Remove all loose material and efflorescence as well as cleaning out missing grout areas – apply Efflorescence Rid using Efflorescence-rid sprayed via a low-pressure sprayer.



- b. Remove all loose & damaged grout, allow area to dry completely
- c. Repeat the application of Efflorescence rid until foaming stops which may require more than 3 passes depending on the amount of efflorescence present.
- d. On completion of last pass with Efflorescence-Rid wash area with clean water. Allow area to dry completely.
- e. Using a “squeeze bottle” pour Sealtight into grout lines and screed where tile grout

has been removed, to the point of flooding the screed.

- f. Allow the Sealtight to dry over a min of 24 hours.
- g. Re-apply tile grout and allow to dry.
- h. Once tile grout is dry, saturate all the tile grout within the entire balcony with Sealtight. Ensure that Sealtight has a min of 24 hours to dry before getting wet.



All technical bulletins are available on our website www.swppl.com.au. Please do not hesitate to contact us should further information be required.

Bruce Leslie - Mobile 0406 137 701 bruce@swppl.com.au

PO Box 694, Padstow NSW 2211, Australia

Phone: +61 (2) 9771 0011